



裸圧着スリーブ(B型/P型)

参考: 富士端子工業株式会社

呼び	L (mm)	D (mm)	d (mm)	電線抱合容量(参考)	
				撚線 mm <sup>2</sup>	
B型	B-1.25	15.0	3.3	1.7	0.25 ~ 1.04
	B-2	15.0	4.0	2.3	1.04 ~ 2.63
	B-5.5	15.0	5.4	3.4	2.63 ~ 6.64
	B-8	21.0	7.0	4.5	6.64 ~ 10.52
	B-14	26.0	8.9	5.8	10.52 ~ 16.78
	B-22	29.0	11.3	7.7	16.78 ~ 26.66
	B-38	32.0	13.2	9.4	26.66 ~ 42.42
	B-60	36.0	15.4	11.4	42.42 ~ 60.57
	B-70	37.0	17.5	13.3	60.57 ~ 76.28
	B-80	38.0	19.4	14.5	76.28 ~ 96.30
	B-100	38.0	22.0	16.4	96.30 ~ 117.20
	B-150	54.0	26.4	19.5	117.20 ~ 152.05
	B-180	57.0	28.5	21.0	152.05 ~ 192.60
	B-200	63.0	32.2	24.0	192.60 ~ 242.27
	B-325	72.0	37.0	28.0	242.27 ~ 325.00

呼び	L (mm)	D (mm)	d (mm)	電線抱合容量(参考)	
				撚線 mm <sup>2</sup>	
P型	P-1.25	8.0	3.3	1.7	0.25 ~ 1.04
	P-2	8.0	4.0	2.3	1.04 ~ 2.63
	P-5.5	8.5	5.4	3.4	2.63 ~ 6.64
	P-8	9.5	7.0	4.5	6.64 ~ 10.52
	P-14	11.0	8.9	5.8	10.52 ~ 16.78
	P-22	13.5	11.3	7.7	16.78 ~ 26.66
	P-38	16.5	13.2	9.4	26.66 ~ 42.42
	P-60	19.0	15.4	11.4	42.42 ~ 60.57
	P-70	19.0	17.5	13.3	60.57 ~ 76.28
	P-80	19.5	19.4	14.5	76.28 ~ 96.30
	P-100	20.0	22.0	16.4	96.30 ~ 117.20
	P-150	27.0	26.4	19.5	117.20 ~ 152.05
	P-180	28.5	28.5	21.0	152.05 ~ 192.60
	P-200	32.0	32.2	24.0	192.60 ~ 242.27
	P-325	37.0	37.0	28.0	242.27 ~ 325.00